





offshore construction and maintenance vessels purpose built for operations. The vessels are fitted with state-of-the-art ROV, A-Frame and Reel Winder system.



- Length 75.50m
- Breadth 17.00m
- Depth Mould 7.50m
- Gross Tonnage 2921 tons (approx.)
- Net Tonnage 876 tons (approx.)
- 200t A-Frame
- 2 x Auxiliary cranes
- Side launched world class ROV system
- Class II DP System

# **SPECIFICATION**





#### **TECHNICAL SPECIFICATION**

Port of Register Port Klang
Designer Conan Wu & Associates Pte Ltd
Classification ABS, Maltase Cross+A1,
FiFi-1, DPS-2 +AMS Anchor Handling/
Offshore Support Vessel
Year Built April 2009
Flag Malaysian

#### PRINCIPAL PARTICULARS

Length O.A. 75.50m Breadth Mould 17.00m Depth Mould 7.50m Design Draft 6.48m Summer Draft 6.00m

Gross Tonnage 2921 Tons (approx.) Net Tonnage 876 Tons (approx.) Free Deck Space 500 m² (approx.)

#### MACHINERY / PROPULSION

Main Engines 2 x Diesel engine BERGEN 2 x 6120 p.s @ 750rps c/w reduction gearbox Propulsion ULSTEIN CPP system

Performance Speed (Designed) Approx. 14.5 knots at 100% MCR Bow Thruster / Stem Thruster 1 eah  $\times$  11 tons capacity electric motor driven Ulstein CPP Tunnel Thruster for bow & stem Retractable Thruster 1  $\times$  13.5 tons Diesel engine driven Ulstein retractable Thruster

Bollard Pull Approx. 150 tons @ 100% MCR Diesel Driven Generators 2 x 590kW, 440/3/60Shaft Alternators 2 x 1730kW, 440/3/60

#### GENERAL

Rescue Boat 1 x FRC Type Rescue boat c/w self launching davit Dynamic Positioning System - 2 1 set USBL System - 2 1 set ROV Mezzanine Deck

#### ACCOMMODATION

2 x 1-Man Cabins (2) 10 x 4-Men Cabins (40) 3 x 2-Men Cabins (6) **Total = 48 men** 

## CARGO / TANK CAPACITY

Fresh Water Tank 760.0 cu. m.

Fresh / Drill Water / SWB Tank 560.0 cu. m.

Fuel Oil Tank 1,150.0 cu. m.

Liquid Mud / Brine Water Tank 720.0 cu. m.

Hydraulic Oil Tank 7.0 cu. m.


Foam Tank 21.0 cu. m.

Dispersant 21.0 cu. m.

Lube Oil Storage Tank 11.0 cu. m.

Dirty Oil Tank 17.0 cu. m. Cement Tank 10,800.0 cu. m.

Lube Oil Storage Tank (M/E) 14.0 cu. m. Lube Oil Storage Tank (G/set) 6.5 cu. m.



## DECK MACHINERY & TOWING / ANCHOR HANDLING EQUIPMENT

**Towing & Anchor Handling Winch** Double Drum Waterfall type low pressure electro hydraulic operated.

Make: BRATVAAG Norway

Towing / Working Drum Capacity 2990 M x 82 mm dia each Winch Load Capacity 350 Tons @ 6m/mins. at low speed Brake Holding 1st layer

Storage Reel Winch Capacity 450 Tons Brake Holding 1 x 3500 m x 82 MM dia @ electro hydraulic system

Gypsy Winch (2) PS @ STB Currently fitted with Gypsy wheels fot 90mm chain, adjustable for 58mm to 12mm chain (350 Tons)

Chain Lockers (2) PS @ STB, 144.45 cu. m. each

Towing Pins sets x 500 Tons

Shark Jaw 4 sets 200 Tons Karmfork Stern Roller 5.500 M (L) x 2.50 M dia.

Acnhor Windlass / Towing Winch 1 x 14 Tons @ electro

hydaulic system

Capstan 2 x 10 Tons @ electro hydaulic system
Tugger Winch 2 x 15 Tons @ electro hydaulic system
Provision Deck Crane 1 x 10 Tons (8m) SWL @ Marine Type

# FIRE FIGHTING EQUIPMENT

External Fire Fighting System FiFi 1 System @  $2 \times 1200$  cu. M3/hr water monitor c/w deck spray system to ABS rules Internal Complies to classification Society & SOLAS requirement